

# TS-15S



► FEATURES

- **Elegant and slim dual tone design**
- **Sharp 500 contrast ratio**
- **High 250 brightness for more vibrant and colorful images**
- **Surface Acoustic Wave (SAW) touch technology**
- **Scratch resistant touch panel**
- **50 million touch stability**
- **Auto-adjustment for optimal setting**
- **User-friendly OSD with lockable key function**
- **Kensington® security socket**
- **VESA compliant for easy wall or arm configuration**



► SPECIFICATION

Panel	<b>Panel Type</b>	TFT LCD
	<b>Panel Size</b>	15.0" (381mm)
	<b>Max. Resolution</b>	XGA 1024 x 768
	<b>Pixel Pitch</b>	0.297mm
	<b>Brightness</b>	250cd/m <sup>2</sup> (Typical)
	<b>Contrast Ratio</b>	500:1 (Typical)
	<b>Surface Treatments</b>	Hard Coating (3H), Anti-glare Treatment
	<b>Viewing Angle (H/V)</b>	130°/120° (Typical)
	<b>Display Color</b>	16.2M
	<b>Response Time</b>	6ms (GTG)
Input	<b>Frequency (H/V)</b>	H: 30kHz - 60kHz V: 50Hz - 75Hz
	<b>Max. Pixel Clock</b>	80MHz
Connector	<b>Life Time</b>	30,000hrs (Minimum)
	<b>Touch Interface</b>	8-Pin Mini Dim
Touch Screen	<b>Analog</b>	15-Pin D-Sub
	<b>Power</b>	3-Pin AC Plug
Tilt	<b>Technology</b>	SAW (Surface Acoustic Wave)
	<b>Optical Transmission</b>	>90%
	<b>Positional Accuracy</b>	<1% Deviation Error
	<b>Panel Resolution</b>	4096 x 4096
	<b>Active Force</b>	<3 ounces
	<b>Panel Interface</b>	RS-232 <small>(An optional serial-USB converter can be provided upon the request)</small>
	<b>Glass Thickness</b>	0.118/3.0mm
	<b>Life Performance</b>	50 million touches at a single point
	<b>Operational Temp.</b>	-20°C to 50°C
	<b>Storage Temp.</b>	-40°C to 71°C
Mounting	<b>Humidity</b>	90% RH at 40°C
	<b>Tilt</b>	+10°
Regulation Approval	<b>VESA FPMPMI</b>	Yes (75mm)
	<b>Certifications &amp; Compliance</b>	UL/CUL, TUV/GS, CB, FCC, CE, EPA, WEEE, RoHS
Power	<b>VESA</b>	DDC 1/2B, DPMS
	<b>Power AC Consumption</b>	100 - 240V, 50 - 60Hz <30W (On) <3W (Stand-by) <3W (Off)
Dimensions	<b>Net (W x H x D)</b>	386 x 360 x 169mm (15.1" x 14.2" x 6.7")
	<b>Packing (W x H x D)</b>	480 x 485 x 210mm (18.9" x 19.1" x 8.3")
Weight	<b>Net Weight</b>	4.6Kg (10.1lbs)
	<b>Gross Weight</b>	6.6Kg (14.5lbs)
Packing	<b>1 Pallet</b>	32 Cartons
	<b>20' Container</b>	320 Sets
	<b>40' Container</b>	640 Sets

All specifications are subject to change without prior notice

[www.agneovo.com](http://www.agneovo.com)

Copyright © 2007 AG Neovo. All rights reserved.  
The name AG Neovo is a trademark of Associated Industries China, Inc.  
All other trademarks are the property of their respective owners.