

X-15



▶ FEATURES

- Distinctive metal housing for added strength
- NeoV Optical Glass™
- Swift 8ms response time
- High 400 brightness
- Crisp 500 contrast ratio
- DVI ready for high quality signal
- S-Video* and CVBS* inputs
- Auto-adjustment for optimal setting
- Kensington® security socket
- VESA standard wall mount
- Available colors: black, white

▶ SPECIFICATION

Panel	Panel Type	TFT LCD	
	Panel Size	15.0" (381mm)	
	Max. Resolution	XGA 1024 x 768	
	Pixel Pitch	0.297mm	
	Brightness	400cd/m ² (Typical)	
	Contrast Ratio	500:1 (Typical)	
	Surface Treatments	Hard Coating (3H), Anti-glare Treatment	
	Viewing Angle (H/V)	140°/125° (Typical)	
	Display Color	16.7M	
	Response Time	8ms (GTG)	
	Frequency (H/V)	H: 30kHz - 60kHz V: 56Hz - 75Hz	
	Max. Pixel Clock	80MHz	
Input	Life Time	50,000hrs (Minimum)	
	Analog	15-Pin D-Sub	
	Digital	24-Pin DVI-D	
	S-Video*	4-Pin Mini Din S-Video	
Connector	CVBS*	CVBS Jack	
	Power	3-Pin AC Plug	
NeoV Optical Glass	Thickness	3.0mm (0.18")	
	Reflection Rate	<1%	
	Transmission Rate	>96%	
	Hardness	>6H (MOH's Rating)	
Tilt	Tilt	0° ~ +20°	
Mounting	VESA FPMPI	Yes (100mm)	
Regulation Approval	Certifications & Compliance	FCC, UL/CUL, TUV/Baurt, CE, BSMI, CB, ISO 13406-2, GOST, EPA, WEEE, RoHS	
	VESA	DDC 2B, DPMS	
Power	Power AC Consumption	100 - 240V, 50 - 60Hz <25W (On) <2W (Stand-by) <1W (Off)	
	Dimensions	Net (W x H x D)	380 x 359 x 155mm (15.0" x 14.1" x 6.1")
		Packing (W x H x D)	445 x 490 x 225mm (17.5" x 19.2" x 8.9")
Weight	Net Weight	4.8Kg (10.6lbs)	
	Gross Weight	7.0Kg (15.4lbs)	
Packing	1 Pallet	40 Cartons	
	20' Container	480 Sets	
	40' Container	1040 Sets	

*Video inputs are optional functions

All specifications are subject to change without prior notice



www.agneovo.com

Copyright © 2007 AG Neovo. All rights reserved.
The name AG Neovo is a trademark of Associated Industries China, Inc.
All other trademarks are the property of their respective owners.